

Plastica Airdomes Order Form

Date

..... /..... /.....

Your Name

.....

Company

.....

Address

.....

.....

.....

.....

Tel. No.

.....

Fax. No.

.....

Your Ref./Order No.

.....

☐ Request for Quotation

☐ An Order

☐ Confirmation of a telephone order

Method of Carriage:

☐ Overnight (at extra cost)

☐ 3 Day Delivery

☐ Collection

Type of Dome Required:

Cable

☐

Water Bag

☐

Tick if fixings **NOT** required (Cable Dome only)

☐

Tick if Blower unit **NOT** required

☐

Colour:

Wall

☐ Clear

☐ Bronze

☐ Blue Tint

☐ Clear standard reinforced

☐ Bronze standard reinforced

☐ Blue Tint standard reinforced

☐ Clear heavy reinforced

Roof

☐ Clear standard reinforced

☐ Bronze standard reinforced

☐ Blue Tint reinforced

☐ Clear heavy reinforced

Skirt/Doors

☐ Blue

☐ White

Dimensions:

Please indicate the position of doors (minimum of 1.5 metres from any corner), air pressure relief valve and give dimensions of the Dome on diagram below.

If the required Dome is not rectangular, please sketch plan on reverse and contact our Production Department for a price and any assistance.

Notes:

It is recommended that a minimum gap of 1 metre is allowed for between the pool side and the dome where access is required. i.e. dome doors and pool ladders.

All Plastica Cable Domes are manufactured with a 0.6m corner mitre.

If a Cable Dome is required, a foundation of at least 15cm deep concrete or similar will be required.

Plastica Sizing Chart

Up to 130 sq.m.

Standard reinforced roof, unreinforced sidewall.

From 130-180 sq.m.

All standard reinforced.

From 180-230 sq.m.

All heavy reinforced.

