Safe System of Work OPERATING AND SAFETY INSTRUCTIONS FOR LOCKING OFF MACHINERY

		Instruction	Understood ✓ or X
	1	Lock off to be instigated by Manager, Supervisor or any TRAINED personal.	
	2	Machine needs to be locked off if you are undertaking any maintenance requiring safety guards being removed or any electrical tasks being done.	
	3	Turn isolator switch to off position and pull out or push in tag at end of switch lever. Put padlock through the tag and close the padlock	
	4	Remove the key and place this in the lock-off box, the keys for this box will be with Mark Oakley and Andy James. This will be situated on the door outside the Moulding/Engineering office. Put the DO NOT OPERATE label on the isolated switch.	
	5	Fill out the lock off padlock logbook situated on Moulding/Engineering office door.	
	6	When you are ready to release the isolator and return the padlock and key, you must sign the book with a date, time and signature.	
onfirm t teps to ne Supe	hat I v ensur ervisor	ed the above training and fully understand every point that was will wear the required PPE equipment when using the above to my own safety. I will ask for further training if I need to and or Manager if there are any issues with the machinery.	machinery and take a will immediately info
	gned: Date:		
confirm e abov nmedia	that I e mad tely o	I have trained the aforementioned person and that they fully underly, have received the required PPE equipment and know from any issues with the machinery or if they require further training the machinery detailed above.	Inderstand how to use v to inform me
ame:			(Authorised Traine