Safe System of Work OPERATING AND SAFETY INSTRUCTIONS FOR BAG SEALER

	Instruction	Understood ✓ or X
1	Explain that safety equipment must be used at all times and why – safety boots must be used at all times when running machines.	
2	Switch on sealer using switch on wall then the switch situated on the machine	
3	Select required lay flat size.	
4	Pull lay flat through clamp on sealer to desired length, press clamp down.	
5	Do not place fingers close to weld bar as burning may occur.	
6	Cut off bag only after the red light has de activated.	
7	Do not use any machine unless trained and authorised by Manager/ Setter.	
onfirm that I eps to ensu e Superviso	ed the above training and fully understand every point that w will wear the required PPE equipment when using the above re my own safety. I will ask for further training if I need to ar or or Manager if there are any issues with the machinery.	e machinery and to nd will immediately
nfirm that I eps to ensu e Superviso	will wear the required PPE equipment when using the above re my own safety. I will ask for further training if I need to ar	e machinery and to nd will immediately
onfirm that I eps to ensu e Superviso ame:	will wear the required PPE equipment when using the above re my own safety. I will ask for further training if I need to are or Manager if there are any issues with the machinery.	e machinery and to
nfirm that I eps to ensure Supervisorame:	will wear the required PPE equipment when using the above re my own safety. I will ask for further training if I need to are or Manager if there are any issues with the machinery.	e machinery and the machinery

Signed Date: