

Pool Covering and Uncovering Procedures for Manual Commercial Static and Mobile Reel Systems

Only trained authorised persons are to operate this equipment

TO COVER THE POOL


1. If Mobile System; position reel system as close to pool edge as possible, fix castors to braked position and secure.
2. If 3:1 reduction gearbox is fitted remove the handle and store safely.
3. Attach tow rope to the pool cover and walk to opposite end of pool.
4. Proceed to pull the pool cover onto the pool surface at an even pace.
5. Remove the tow rope and store safely away.

Piggyback systems Only

6. Return to reel system, detach webbing straps from reel system tube, carefully release braked castors and move the reel system to the other side of the pool. Fix castors to braked position and secure.
7. Repeat stages 2, 3 and 4 as above.
8. Remove the tow rope and store safely away.

TO UNCOVER THE POOL

1. If Mobile System; ensure reel system is secured in position.
2. If 3:1 reduction gearbox is fitted attach winding handle.
3. Ensure the blue top surface of the cover is wound on top as shown opposite.
4. Proceed to 'wind in' cover at an even pace until completely wound onto reel and secure.
5. If Mobile System; carefully release braked castors and move into storage position. Fix castors to braked position and secure.



Do not allow people to sit on reel system.

Ensure the reel system's framework is regularly washed down with fresh water to remove pool water deposits and protect the surface.

Ensure the pool cover is washed down and cleaned with fresh tap water on a regular basis as it is removed from the pool.

Report any defect to your supervisor immediately for attention.

